



Next Generation High Performance GNSS Receiver

Benefits

Innovative OEM6™ technology

Supports current and future GNSS signals

Application-based configurations

Designed for rapid integration

Features

Low power consumption

Flexible communication interfaces

Software configurable performance

Ultra-light

High position accuracy and availability

Designed with the Future in Mind

The OEM628 is designed with NovAtel's new 120 channel ASIC, which tracks all current and upcoming GNSS constellations and satellite signals including GPS, GLONASS, Galileo and Compass. Configurable channels optimize satellite availability in any condition, no matter how challenging. Already tracking GPS L5 and Galileo GIOVE-A/B test satellites, the OEM6 is software upgradable to track future signals as they become available. Maximizing satellite availability and optimizing GNSS signal usage now, and in the future, ensures consistent, high performance GNSS positioning.

Easy System Integration

Like all NovAtel products, the OEM628 is designed and built with a focus on product quality and ease of integration. It maintains our industry-setting V2 form factor ensuring a successful drop-in replacement and backwards compatibility for existing customers. A development kit and user-friendly configuration software is available to assist new customers with rapid integration and faster time to market. NovAtel's well-established, comprehensive set of software commands facilitates system integration. Ethernet and NTRIP 2.0 Client and Server connectivity is offered in addition to our traditional communications interfaces.

Flexible Configurations for your Application

Proven and innovative new NovAtel technology combine to achieve the best in GNSS positioning. NovAtel's industry-leading Pulse Aperture Correlator multipath mitigation technology is standard and ensures the highest quality measurements and positioning. Innovative new technology provides excellent resistance to interference for consistent, accurate and reliable positioning. Configurable options ensure that your positioning and accuracy needs are being met at all times. To learn more about how our firmware options can enhance your positioning, please visit www.novatel.com/products/firmware-options.

If you require more information about our receivers, visit novatel.com/products/gnss-receivers/oem-receiver-boards



novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)

or 403-295-4900

China 0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Performance¹

Channel Configuration

120 Channels²
 Signal Tracking
 GPS: L1, L2, L2C, L5
 GLONASS: L1, L2
 Galileo: E1, E5³
 GIOVE-A/GIOVE-B (test)
 Compass⁴
 SBAS
 L-band

Horizontal Position Accuracy (RMS)

Single point L1	1.5 m
Single point L1/L2	1.2 m
SBAS ⁵	0.6 m
DGPS	0.4 m
OmniSTAR	
VBS	0.6 m
XP	0.15 m
HP	0.1 m
RT-20 ^{®6}	0.2 m
RT-2™	1 cm+1 ppm
Initialization time	<10 s
Initialization reliability	> 99.9%

Measurement Precision (RMS)

Fully independent code and carrier measurements:

	GPS	GLO
L1 C/A code	4 cm	8 cm
L1 carrier phase	0.5 mm	1.0 mm
L2 P(Y) code ⁷	8 cm	8 cm
L2 carrier phase ⁷	1.0 mm	1.0 mm
L2C code ⁸	8 cm	8 cm
L2C carrier phase ⁸	0.5 mm	0.5 mm
L5 code	3 cm	-
L5 carrier phase	0.5 mm	-

Maximum Data Rate⁹

Measurements	100 Hz
Position	100 Hz

Time to First Fix

Cold start ¹⁰	<50 s
Hot start ¹¹	<35 s

Signal Reacquisition

L1	<0.5 s (typical)
L2	<1.0 s (typical)

Time Accuracy¹² 20 ns RMS

Velocity Accuracy 0.03 m/s RMS

Velocity¹³ 515 m/s

Physical and Electrical

Dimensions 60 x 100 x 9.1 mm

Weight 37 g

Power

Input voltage +3.3 VDC [+5%/-5%]
 Power consumption¹⁴ 1.3 W

Antenna LNA Power Output

Output voltage 5 VDC [+5%/-5%]
 Maximum current 100 mA

Connectors

Main 24-pin dual row male header
 Aux 16-pin dual row male header
 Antenna input MMCX female
 External oscillator input MMCX female

Communication Ports

1 RS-232	300 to 921,600 bps
2 LVTTTL	300 to 921,600 bps
2 CAN Bus ¹⁵	1 Mbps
1 USB port	12 Mbps

1 LAN Ethernet port supporting:
 -10BaseT/100BaseT networks
 -Direct TCP/IP & UDP connectivity
 -NTRIP (v2.0) client and server

Pulse per second output
 Event marker input support

Environmental

Temperature

Operating	-40°C to +85°C
Storage	-40°C to +85°C

Humidity 95% non-condensing

Vibration

Random vibrate MIL-STD 810G
 (Cat 24, 7.7 g RMS)
 IEC60068-2-6
 Sine vibrate IEC60068-2-6

Bump IEC9022-31-06 (25 g)

Shock MIL-STD-810G (40g)
 Survival (1000g)

Features

- Field-upgradeable software
- 20 Hz measurement and position data rate
- PAC multipath mitigating technology
- Differential GPS positioning
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, CMR, CMR+ and RTCA
- Navigation output support for NMEA-0183 and detailed NovAtel ASCII and binary logs
- Auxiliary strobe signals, including a configurable PPS output for time synchronization and mark inputs
- Outputs to drive external LEDs
- External oscillator input

NovAtel Connect

NovAtel Connect is an intuitive configuration and visualization tool suite allowing comprehensive control of the OEM628 product.

- Easy to use wizards guide you through positioning mode configuration and raw data collection
- Detailed graphical windows display comprehensive status information
- Plan view and playback files allow you to monitor the positioning and configuration history
- Remotely control and monitor the OEM628 over the internet
- Available on Windows XP, Windows 7 and Linux platforms

Firmware Options

- RT-2
- RT-20
- OmniSTAR® HP, XP, VBS, G2
- ALIGN®
- GL1DE®
- RAIM
- 100 Hz output rate⁹

Additional Accessories

- GPS-700 series antennas
- ANT series antennas
- RF cables—5, 10 and 30 m lengths
- OEM6 Development Kit



Version 4 - Specifications subject to change without notice.
 © 2011 NovAtel Inc. All rights reserved.
 NovAtel, GL1DE, ALIGN and RT-20 are registered trademarks of NovAtel Inc.
 RT-2, OEM6 and OEM628 are trademarks of NovAtel Inc.
 OmniSTAR is a registered trademark of OmniSTAR Inc.
 Printed in Canada.
 OEM628 September 2011 D15588
 For the most recent details of this product:
novatel.com/assets/Documents/Papers/OEM628.pdf

¹ Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.
² Tracks up to 60 L1/L2 satellites.
³ Includes ESa, ESb and Alt-BOC.
⁴ The Compass signal is not finalized and changes in the signal structure may still occur. Designed for Compass Phase 3 compatibility.
⁵ GPS only.
⁶ Expected accuracy after static convergence.
⁷ L2 P for GLONASS.
⁸ L2 C/A for GLONASS.
⁹ 100 Hz while tracking up to 20 satellites.
¹⁰ Typical value. No almanac or ephemerides and no approximate position or time.
¹¹ Typical value. Almanac and recent ephemerides saved and approximate position and time entered.
¹² Time accuracy does not include biases due to RF or antenna delay.
¹³ Export licensing restricts operation to a maximum of 515 metres per second.
¹⁴ Power consumption values for GPS L1/L2 with Ethernet disabled.
¹⁵ User application software required.

